



P.C.B  
LAYOUT  
TOP  
VIEW



SCHEMATIC



**SPECIFICATION**  
 1. Rating : DC 30V 0.5A;  
 2. Contact resistance:  $\leq 30m\Omega$ ;  
 3. Insulation resistance:  $\geq 100M\Omega$  (DC250V);  
 4. Withstand voltage: 500VAC ;  
 5. Insertion and extraction Force: 3-30N;  
 6. Life test: 5,000 cycles.

7	HOUSING	1	PC	
6	CAP	1	BRASS	Ni-Plating
5	AXIS SUPPORT	1	BRASS	Ni-Plating
4	PIN	1	BRASS	Ni-Plating
3	FLAT PIECE	1	BRASS	Ag-Plating
2	CURVE PIECE	1	BRASS	Ag-Plating
1	SPRING	1	BRONZE	Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

UNIT: MM	TYPE:	MODEL NO:	PAPER NO:	PAGE 1 OF 1
	DC JACK	DC0035A	TOLERANCE	SCALE
			±0.3	1:1
			±2'	VER
				1

DESIGNER  
 BY:  
 CHECK  
 BY:  
 APPROVED  
 BY:

淮洋有限公司 HUAI YANG CO., LTD.  
 www.hy1688.com.tw TEL:886-2-82618986