




PJ3093C 3.5mm PHONE JACK (SMD)



P.C. B Layer (copper side view)



L=1.2	PJ3093C-D	PJ3093C-E	PJ3093C-F	PJ3093C-G	PJ3093C-H	PJ3093C-I	PJ3093C-J
L=1.4	PJ3093C-K	PJ3093C-L	PJ3093C-M	PJ3093C-N	PJ3093C-O	PJ3093C-P	PJ3093C-Q
L=0.8	PJ3093C-R	PJ3093C-S	PJ3093C-T	PJ3093C-U	PJ3093C-V	PJ3093C-W	PJ3093C-X
Schematic							
L=1.2	PJ3093C-B	PJ3093C-C	PJ3093C-D	PJ3093C-E	PJ3093C-F	PJ3093C-G	PJ3093C-H
L=1.4	PJ3093C-I	PJ3093C-J	PJ3093C-K	PJ3093C-L	PJ3093C-M	PJ3093C-N	PJ3093C-O
L=0.8	PJ3093C-P	PJ3093C-Q	PJ3093C-R	PJ3093C-S	PJ3093C-T	PJ3093C-U	PJ3093C-V
Schematic							

技術指標：			
使用溫度範圍	-30-70℃	耐壓	AC500V(50Hz)/min
額定負荷	DC 30V 0.5A	動作力	3~20N
接觸電阻	≤0.03Ω	壽命	5000 次
絕緣電阻	≥100MΩ		