


Type MAF

Fast Acting Radial Lead Micro Fuse Series



Approvals

UL Listed 50mA~10A
CSA Certified 50mA~6.3A

Electrical Characteristics

Rated Current	1.0 In	2.0 In
	MIN	MAX
50mA~5A	4 hours	60sec

Interrupting Ratings

50 amperes at 250V AC.

Environmental Specification

Operating Temperature

-55°C to +125°C

Shock

MIL-STD-202, Method 213, Condition 1 (Saw tooth)

Vibration

MIL-STD-202, Method 201(10-55 Hz x 3axis/no load)

Salt Spray

MIL-STD-202, Method 101, Test Condition B (48Hrs)

Insulation Resistance

MIL-STD-202, Method 302, Test Condition A
(After Opening) 10,000 ohms minimum


Resistance to Solder Heat

MIL-STD-202, Method 210, Test Condition F
(10sec, at 260°C)


Thermal Shock:

MIL-STD-202, Method 107, Test Condition B
(-65°C to +125°C)

Mechanical Dimensions



BOX SIZE 336mm*261mm*40mm



Physical Specification

Materials

Base and Cap: Black thermoplastic
Pin: Tin-lead plated alloy

Packaging

1. In bulk: 1,000 pcs per box.
2. On Tap: Ammo pack, 1,000 pcs box