



Feature -

Rating : 1.7A , 13VDC

SP2T or 2P2T

Switch Applications -

Automotive

Consumer products

Instrumentation


Computer products

Communication equipment

► SPECIFICATIONS


SWITCH SPECIFICATIONS	
POLE - POSITION	1P2T or 2P2T , Lock type are Available
CONTACT RATING	13 V DC , 1.7 A
CONTACT RESISTANCE	50 mΩ MAX. 1.5 V DC ; 100 mA , by method of voltage DROP
INSULATION RESISTANCE	100 MΩ MIN. 500 V DC
DIELECTRIC STRENGTH	Breakdown is not allowable ; 500 V AC for 1 minute
OPERATING FORCE	400 ± 200 gf
OPERATING LIFE	10,000 cycles
OPERATING TEMPERATURE RANGE	-20°C ~ 70°C
TOTAL TRAVEL	3.5 ± 0.3 mm

► HOW TO ORDER



► DIMENSION


PS018-N22AAA




► MATERIAL

- ACTUATOR : PA + GF
- TERMINAL : BRONZE SILVERPLATING
- FRAME : PA + GF
- SPRING : STAINLESS STEEL

► P.C.B LAYOUT



► SCHEMATIC



► UNIT WEIGHT

- PS018-N22AAA : 2.1 ± 0.05 g / pc