



淮 洋 有 限 公 司 HUI YANG CO.,LTD.

TEL : 886-2-8261-8986 FAX : 886-2-8261-1885

www.hy1688.com.tw 236新北市土城區中央路二段191號10樓之5

R-18-32A Push Button Switch

Applications: Various electronic appliances



Specification:





1. Circuit : (ON) – OFF
2. Rating: 1A125VAC
3. Contact resistance: 30m ohm Max.
4. Insulation resistance DC 500V
100M Ω Min.
5. Dielectric strength: AC 500V 1
minute.
6. Electrical life: 10,000 cycles Min
7. Operating force: 300 ± 50 g
8. Button color: red, yellow, green,
blue, white, black, orange
9. Operating temperature range: -25°C
 $\sim +85^{\circ}\text{C}$

How to order: for example R-18-32A-R


Model Number	Cap color
R-18-32A-R	Red
R-18-32A-Y	Yellow
R-18-32A-O	Orange
R-18-32A-K	Black
R-18-32A-N	Green
R-18-32A-B	Blue
R-18-32A-W	White

Specifications:

- 1.Circuit: Push A:(ON)–OFF
- 2.Rating: AC 125V 1A
- 3.Contact Resistance: DC 5V 1A 30mΩ (max.)
- 4.Insulation Resistance: DC 500V 100MΩ (min.)
- 5.Withstand Voltage: AC 500V 1 Minute
- 6.Operating Force: 300±50g
- 7.Life Cycle: 10,000 Cycles



SCHEMATIC



LAYOUT

TYPE	PUSH BUTTON SWITCH	UNIT	mm	SCALE	N/A	DATE	950928
MODEL	R-18-32A	DESIGN		DRAWN	Ting	AUDIT	LIU