


Feature :

- Touch Sensor option, tactile feedback operation with travel
- Long life operation, cost effective , dust proof
- Customer symbol , knob, PCB module set solution
- Easy assembly for production process
- Anti-light leakage design

Application :

- Audio / video switchers
- Instrumentation
- Communication equipments



- TACT SWITCH
- PUSH SWITCH
- LED SENSOR SWITCH
- 5 DIRECTION NAVIGATION SWITCH WITH LED
- MEMBRANE SWITCH
- LED LIGHT BAR
- SLIDE SWITCH
- ROTARY SWITCH
- ROCKER SWITCH
- DETECT SWITCH
- ENCODER
- INTERRUPTER
- MINIATURE MICRO SWITCH
- TELEPHONE HOOK SWITCH
- DOOR SWITCH
- MINI SIZE SOCKET
- KNOB
- CAP SYMBOL

SWITCH SPECIFICATIONS	
POLE - POSITION	OFF - <ON> for Momentary Type , SPST
CONTACT RATING	100mA 12 VDC
CONTACT RESISTANCE	200 mΩ MAX.
INSULATION RESISTANCE	500 MΩ MIN. 500 V DC
DIELECTRIC STRENGTH	Breakdown is not Allowable ; AC 500V (50-60HZ) for 1 Minute
OPERATING FORCE	200 ± 100 gf
OPERATING LIFE	1,000,000 cycles MIN.
OPERATING TEMPERATURE RANGE	-40°C ~ 85°C
TOTAL TRAVEL	1.5 ± 0.3 mm

HOW TO ORDER

