



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 100V
 OPERATION TEMPERATURE: -0°C~+50°C

PART NUMBER

22MBH - 0 5 * T - 1 2 1 L *

SERIES ————
 NO. OF POS. ————
 CONTACT PLATED OPTION ————
 1: GOLD FLASH
 6: 30u" GOLD

COLOR OPTION
 BLANK: BLACK
 BE: BEIGE

LEAD FREE

TAPE REEL PACKAGE

TIN PLATING ON SOLDER TAIL

淮洋有限公司 HUAI YANG CO., LTD.		SERIES: USB CONNECTOR SERIES			
		TITLE: MINI USB B TYPE, PCB MOUNT, SMT, METAL SHIELD, FEMALE			
LINEAR: .X±0.30 .XX±0.20 .XXX±0.10	APPROVALS	SIZE: A4	VERSION: A	DWG NO. 22MB-002	
ANGLES: ±3°	DRAWN: <i>Lion</i>	SCALE: NONE	UNIT: mm	SHEET: 1 OF 1	
	CHECKED: <i>Eric</i>				
	APPROVED: <i>James</i>				

A	RELEASE	2008.9.23
REV.	DESCRIPTION	DATE