



P.C.B LAYOUT  
TOP VIEW ±0.05

PART NUMBER

22MNH - 0 5 \* T - 1 1 1 L

SERIES NO. OF POS. CONTACT PLATED OPTION  
1: GOLD FLASH  
6: 30u" GOLD

LEAD FREE TAPE REEL PACKAGE TIN PLATING ON SOLDER TAIL

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)  
SHELL: COPPER ALLOY, NICKEL PLATING  
TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX  
DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE  
CONTACT RESISTANCE: 50m OHMS MAX  
INSULATION RESISTANCE: 100M OHMS MIN AT DC 100V  
OPERATION TEMPERATURE: -0°C~+50°C

淮洋有限公司 HUAI YANG CO., LTD.		SERIES: USB CONNECTOR SERIES	
LINEAR: .X±0.30 .XX±0.20 .XXX±0.10 ANGLES: ±3°		TITLE: MINI USB, B TYPE, PCB MOUNT, VERTICAL, METAL SHIELD, FEMALE	
APPROVALS DRAWN: <i>Lion</i> CHECKED: <i>Eric</i> APPROVED: <i>James</i>		SIZE: A4	VERSION: A
10026		DWG NO. 22MN-002	SCALE: NONE
		UNIT: mm	SHEET: 1 OF 1

A	RELEASE	2008.12.17
REV.	DESCRIPTION	DATE

1

2

3

4